

REQUIREMENTS	PROPOSED
<i>ESCORT REQUIREMENTS - <u>WIDTH</u> - 2-LANE HWY</i>	12' TO 14' - 1 FRONT ESCORT > 14' - 1 FRONT ESCORT & 1 REAR ESCORT
<i>ESCORT REQUIREMENTS - <u>WIDTH</u> - MULTIPLE LANE HWY</i>	12' TO 14' - 1 REAR ESCORT > 14' - 1 FRONT ESCORT & 1 REAR ESCORT
<i>ESCORT REQUIREMENTS - <u>HEIGHT</u> - 2- LANE HWY</i>	≥ 14'
<i>ESCORT REQUIREMENTS - <u>HEIGHT</u> - MULTIPLE LANE HWY</i>	
<i>ESCORT REQUIREMENTS - <u>LENGTH</u> - 2- LANE HWY</i>	> 90'
<i>ESCORT REQUIREMENTS - <u>LENGTH</u> - MULTIPLE LANE HWY</i>	

<i>FLAG SIZE</i>	18" X 18" MINIMUM
<i>FLAG COLOR</i>	FLORESCENT RED OR FLORESCENT ORANGE PURSUANT TO TITLE 49 CFR 393.87 STANDARD
<i>TRANSPORT # & LOCATION</i>	MIN. REQUIREMENTS PURSUANT TO TITLE 49 C.F.R. 393.87
<i>ESCORT # & LOCATION</i>	NO REQUIREMENTS

<i>DAYS AND HOURS OF OPERATIONS</i>	MIN. - SUNRISE TO SUNSET - MONDAY THROUGH SATURDAY; SUNDAY - STATES MAKE DETERMINATION
-------------------------------------	--

<i>SIGN/BANNER MESSAGE</i>	OVERSIZE LOAD
<i>OVERSIZE LOAD SIGN/BANNER COLOR</i>	BLACK LETTERS ON YELLOW BACKGROUND
<i>OVERSIZE SIGN/BANNER SIZE</i>	18" X 7'
<i>SIZE OF LETTERS</i>	10" X 1.4" - 1.5"
<i>OVERSIZE LOAD SIGN/BANNER LOCATION</i>	FRONT & REAR OF TRANSPORTING VEHICLE WHERE LICENSE PLATE AND LIGHTS ARE NOT BLOCKED; FRONT & REAR OF ESCORT OR ABOVE ROOFLINE OF ESCORT WHERE IT IS VISIBLE FROM FRONT & REAR

<i>TRANSPORT WARNING LIGHTS</i>	MINIMUM : FLASHING OR STROBE AMBER LIGHT; SHOULD BE VISIBLE FOR 500', 360°
<i>ESCORT WARNING LIGHTS</i>	MINIMUM : FLASHING OR STROBE AMBER LIGHT; SHOULD BE VISIBLE FOR 500' 360°